

## Subpart I - Standards of performance for Hot Mix Asphalt Facilities

### Applicability - §60.90

General	<ol style="list-style-type: none"><li>1.) Facilities affected are each hot mix asphalt facility. For the purpose of this subpart, a hot mix asphalt facility is comprised only of any combination of the following: dryers; systems for screening, handling, storing, and weighing hot aggregate; systems for loading, transferring, and storing mineral filler, systems for mixing hot mix asphalt; and the loading, transfer, and storage systems associated with emission control systems.</li><li>2.) Any facility that commences construction or modification after June 11, 1973, is subject to the requirements of this subpart.</li></ol>
---------	---

### Emission Standards - §60.92

Source	All Emissions
General	<ol style="list-style-type: none"><li>1.) Facility shall not emit gases which contain particulate matter in excess of 90 mg/dscm (0.04 gr/dscf).</li><li>2.) Facility shall not emit gases which exhibit 20 percent opacity, or greater.</li></ol>

### Test Methods and Procedures - §60.93

Source	All Emissions
General	<ol style="list-style-type: none"><li>1.) Facility shall use as reference methods and procedures the test methods in Appendix A of this part or other methods and procedures as specified in this section, except as provided in §60.8(b).</li><li>2.) Facility shall determine compliance with the particulate matter standards in §60.92 using Method 5 to determine the particulate matter concentration. The sampling time and sample volume for each run shall be at least 60 minutes and 0.90 dscm (31.8 dscf).</li><li>3.) Method 9 and the procedures in §60.11 shall be used to determine opacity.</li></ol>