

## Chapter 6: EMERGENCY VEHICLES (FIRE APPARATUS)

This chapter describes the minimum criteria and requirements for Carl Moyer Memorial Air Quality Standards Attainment Program (Carl Moyer Program) fire apparatus projects.

\*\*\*\*\*

### C. Project Criteria

#### 1. General Criteria

The minimum qualifications for fire apparatus replacement are listed below. All projects must also conform to the requirements in Chapter 2: General Criteria, and in Chapter 3: Program Administration. Participating air districts retain the authority to impose additional requirements in order to address local concerns.

- (A) Eligible Vehicles: Authorized emergency vehicles as described in the California Vehicle Code, sections 27156.2 and 165 including, but not limited to pumpers, ladder trucks, and water tenders are eligible for funding.

\*\*\*\*\*

- (D) Intended Service Class Flexibility: Engines certified to the MHD service class (i.e., GVWR between 14,000 and 33,000 pounds) must be installed in a MHD vehicle as shown on the engine certification EO. However, MHD engines may be installed in a vehicle with a GVWR up to ~~33,600~~ 36,300 pounds (10 percent higher than ~~36,300~~ 33,000 pounds GVWR) with written warranty verification by the engine and chassis manufacturer. A copy of the written warranty verification must be maintained in the air district project file.

Engines certified to the HHD service class (i.e., GVWR greater than 33,000 pounds) may be installed in a vehicle no less than GVWR 29,701 pounds (10 percent lower than 33,001 GVWR).

\*\*\*\*\*