California Environmental Protection Agency AIR RESOURCES BOARD	HARLEY-DAVIDSON MOTOR COMPANY	Executive Order: M-005-0169-1 New On-Road Motorcycles/Engines Page 1 of 3

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the engine and emission control systems produced by the manufacturer are certified as described below for on road motorcycles. Production vehicles shall be in all material respects the same as those for which certification is granted. The manufacturer shall ensure that character "C" or "3" is not used in the eighth (8th) position of the vehicle identification number (VIN) of all vehicles in the engine family listed below. Violation of this VIN provision may result in incorrect registration of the vehicles

Model Year	Engine Family	Vehicle Category	Fuel Type(s)	Strokes per cycle
2011	BHDXC1.80AED	HMC-III	GAS	4

Special Features & Emission Control Systems (ECS)	Engine(cc)
TWC, 2O2S, SFI	1802, 1584, 1688

The following are the exhaust hydrocarbon plus oxides of nitrogen (HC+NOx) and carbon monoxide (CO) standards, or designated or HC+NOx standard as applicable, and certification levels in grams per kilometer (g/km), and evaporative standard and certification level in grams per test (g/test) for this engine/evaporative family. The designated or HC+NOx standard, as applicable, shall be listed on the permanent tune-up label.

Exhaust Emissions (G/KM)			
Pollutant	CERT	STD	DES_STD
HC	0.25	*	*
HC+NOx	0.35	0.8	0.5
CO	4.6	12	

Diurnal and Hot Soak: Hydrocarbon Emissions (g/test)		
Evaporative Family (EVAP)	CERT	STD
BHDXU0025ACA	0.3	2.0

BE IT FURTHER RESOLVED: That certification to the designated HC or HC+NOx standard listed above, as applicable, is subject to the following terms, limitations and conditions. The designated HC or HC+NOx standard shall be the exhaust emission limit for this engine family and cannot be changed during the model year. It serves as the HC or HC+NOx exhaust standard applicable to this engine family for determining compliance with Title 13, California Code of Regulations, Sections 1958(b) and 2101.

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all materials required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Sections 2035 et seq.).

BE IT FURTHER RESOLVED: That because the listed motorcycles are certified to 0.2 grams per test or more below the applicable evaporative standard, the vehicles are exempt from complying with the Air Resources Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" pursuant to Executive Order G-70-16-E.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order M-005-0169 dated June 25, 2010.

This Executive Order is only granted to the engine family and model-year listed above. Vehicles in this family that are produced for any other model-year are not covered by this Executive Order.

See Attachment A for vehicle descriptions.

Executed at El Monte, California on this 22 day of November 2011.

Annette Hebert, Chief
Mobile Source Operations Division

ATTACHMENT A

Make	Model	Engine (cc)	EIM (kg)	TRANS	ECS	EVAP
HARLEY-DAVIDSON	CVO ROAD GLIDE ULT	1802	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	CVO STREET GLIDE	1802	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	CVO ULTRA CLASSIC	1802	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ELECTRA GLIDE CLAS	1584	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ELECTRA GLIDE CLAS	1688	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ELECTRA GLIDE ULTR	1688	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ELECTRAGLIDE POLICE	1688	500	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ESCORT	1688	500	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	R.KING CLASSIC 103	1688	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ROAD GLIDE CUSTOM	1584	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ROAD GLIDE CUSTOM	1688	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ROAD GLIDE ULTRA	1584	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ROAD GLIDE ULTRA 1	1688	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ROAD KING	1584	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ROAD KING CLASSIC	1584	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ROAD KING POLICE	1688	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ROAD KING SHRINE	1584	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ROADKING 103	1688	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ROADKING103 SHRINE	1688	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	STREET GLIDE	1584	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	STREET GLIDE TRIKE	1688	620	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	STREET GLIDE103	1688	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	TRI GLIDE ULTRA CL	1688	620	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ULTRA CLASSIC ELEC	1584	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA
HARLEY-DAVIDSON	ULTRA CLASSIC ELEC	1688	510	M6	TWC, 2O2S, SFI	BHDXU0025ACA

ABBREVATIONS:

GENERAL: 13 CCR 1958, etc.=Title 13, California Code of Regulations, Section 1958, etc.; 40 CFR86.401-90, etc.=Title 40, Code of Federal Regulations, Section 86.401-90, etc.;

HIGHWAY MOTORCYCLE & OFF-HIGHWAY RECREATIONAL VEHICLE CATEGORIES: ATV or ATVA=all terrain vehicle conforming to the California definition in 13 CCR 2411(a); ATVB=Off-highway or non-road recreational vehicles that meet USEPA definition for an all-terrain vehicle or USEPA definition for an off-road utility vehicle and, in addition, meet one or more CARB definitions for an all terrain vehicle, off-road utility vehicle, off-road sport vehicle, and/or sand car; EGC=electric golf cart; HMC=on-road or highway motorcycle; HMC-IA / -IB=HMC below 50 cc / 50 cc to below 170 cc; HMC II=HMC 170 cc to below 280 cc; HMC-III=HMC 280 cc and above; OFMC=off-road motorcycle; SC=sand car above 1000 cc; OFRSV=off-road sport vehicle, including otherwise sand car but with 1000 cc engine or smaller; OFRUV=off-road utility vehicle;

FUEL TYPES: CLNG=natural gas in either CNG or LNG form; CNG / LNG=compressed / liquefied natural gas; DF_CNG/GAS=dual-fuel CNG or gasoline, etc; DSL=diesel; GAS=gasoline; LPG=propane or liquefied petroleum gas;

EMISSION CONTROL SYSTEMS & SPECIAL FEATURES: AFS / HAFS=air fuel ratio sensor / heated AFS; (prefix) 2, 3, 4=2, 3, or 4 catalysts, sensors, TC, SC, CAC, etc. in parallel arrangement; (parenthetic suffix) (2), (3), (4)=2, 3, or 4 catalysts, sensors, TC, SC, CAC, etc. in series arrangement; AIR / PAIR=secondary / pulsed air injection; CAC=charge air cooler; DDI / IDI=direct / indirect diesel injection; EGR=exhaust gas recirculation; EM=engine modification; O2S / HO2S=oxygen sensor / heated O2S; OC=oxidation catalyst; TC=turbocharger; TBI / MFI / SFI / DGI=throttle body / multi port / sequential / direct gasoline fuel injection; TRANS=transmission type; TWC=three way catalyst; SC=supercharger; TWC+OC=TWC plus OC in same container; (prefix) WU=warm-up catalyst;

CERTIFICATION EMISSION LEVELS & STANDARDS: bhp=brake hp; cc=cubic centimeter; CERT=certification emission level; CID=cubic inch displacement; CO=carbon monoxide; CO2=carbon dioxide; D+HS=diurnal plus hot soak evaporative emissions; DES_STD=manufacturer designated standard; EIM=equivalent inertia mass; EVAP=evaporative family; FEL=family emission limit; g=gram; gal=gallon; g/bhp-hr=grams per brake horsepower-hour; g/km=grams per kilometer; g/kW-hr=grams per kilowatt-hour; g/m2-day=grams per square meter per day; g/test=grams per test; HC=(total) hydrocarbons; hp=horsepower; hr=hour; K=1000 miles; kg=kilograms; km=kilometer; kW=kilowatt; L=liter; m2=square meter; mi=mile; mg=milligram; NOX=oxides of nitrogen; NMHC=non methane hydrocarbons; PEVAP=permeation evaporative family; STD=emission standard; *=not applicable; (superscript) o=degree (temperature); oF=degree Fahrenheit; oC=degree Celsius.