

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE ¹	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS ²	ECS & SPECIAL FEATURES ³	DIAGNOSTIC ⁶
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL ⁵		ADDITIONAL IDLE EMISSIONS CONTROL ⁵					
Exempt		N/A					
ENGINE (L)		ENGINE MODELS / CODES (rated power, in hp)					
11.1		See attachment for engine models and codes					

* =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter, hp=horsepower, kw=kilowatt, hr=hour;
¹ CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi-fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;
² L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;
³ ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction - urea / -- ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAPS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SF/MF=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;
⁵ ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS=internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);
⁶ EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses).⁴

in g/bhp-hr	NMHC		NOx		NMHC+NOx		CO		PM		HCHO	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	*	*	*	*	*	*	*	*	*	*
CERT	0.08	0.002	0.16	0.12	*	*	0.1	0.03	0.001	0.001	*	*
NTE	0.21		0.30		*		19.4		0.02		*	

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models have been conditionally certified using the small volume manufacturer provision such that the manufacturer shall submit proper justification that complies with the use of assigned exhaust emission deterioration factors for certification. The additional required documentation shall be submitted within 90 days of this Executive Order signing date. If the manufacturer fails to provide proper justification within aforementioned period, then this Executive Order is hereby null and void and all engines sold under this Executive Order are hereby deemed as uncertified engines.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 30 day of June 2010.


Annette Hebert, Chief
Mobile Source Operations Division

A-376-0003

ATTACHMENT

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lb/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lb/hr)@peak torque	9.Emission Control Device Per SAE J1930
ADICH11.1EEA	EEEEBB	GL11K	286@2200		115	904@1260		71	ECM, TC, SCR, OC, CAC, SCR, ABS
ADICH11.1EEA	EEEEBC	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBD	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBE	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEFF	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBG	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBH	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBI	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBJ	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBK	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBL	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBM	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBN	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBO	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBP	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBQ	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBR	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBS	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBT	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBU	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBV	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBW	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBX	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBY	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,
ADICH11.1EEA	EEEEBZ	GL11K	286@2200		115	904@1260		71	TC, SCR, OC,