State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-304-1
Relating to Certification of New Motor Vehicles

DABRYAN COACH BUILDERS, INC.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1991 model DaBryan Coach Builders, Inc. exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: MY24.6V5FDC9 Displacement: 4.6 Liters (281 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Exhaust Gas Recirculation
Dual Heated Oxygen Sensors
Dual Three-Way Catalysts (Two)
Sequential Multipoint Electronic Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The emission standards for this engine family in grams per mile are as follows:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
0.39	7.0	0.7

The certification emission values for this engine family in grams per mile are as follows:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
0.20	2.7	0.4

BE IT FURTHER RESOLVED: That the listed models are certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Code of Regulations which includes recall liability up to 7 years or 75,000 miles for emission control components if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying to the optional NOx standard for passenger cars with a loaded vehicle weight over 5,250 pounds (Title 13, California Code of Regulations, Section 1960.1.5(a)(1)(C)).

BE IT FURTHER RESOLVED: That the vehicle models listed also comply with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." for the aforementioned model year (Title 13, California Code of Regulations, Section 1968).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2290).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 11th day of March, 1992.

R. B. Summerfield
Assistant Division Chief
Mobile Source Division

199/ AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET E.O.# A-304-1 Page 1

Manufacturer DaBryan Coach Builders, Inc. Engine Family MY24.6V5FDC9

Pass Car X Li-Duty Truck ____ Med-Duty Vehicle ____ Fuel Type Gasoline

Engine Config. V-8 Liter (CID) 4.6 (280.7) Evaporative Family HM

Exhaust ECS & Special Features (incl. CARB, MPI, etc.) EGR/2HO2S/2TWC(2)/SMPI
(Use abbreviations per SAE J1930 JunBB)

Engine: Front X Mid. ___ Rear ___ Drive: FWD ___ RWD X 4WD-FT ___ 4WD-PT ___

Eng. Code/ (Cert. Std.)	Veh. Models (If Coded see Attachmt.)	Trans. Type: A-Auto M-Man.	Equiv. Test Weight	RLHP	Ign.Sys. (PCME/PRDM) Part No.	EGR Syst. Part No.	Catalyst Part No.
118SR05A	"26"	A-4	[5250]	14.6[1]	-12A650-FIMF-FC FIMF-FD (alt)	-9D475-E9SE-BA (alt)	FIVC-GA (-5E212-) FIVC-GA (-5E214-)
	"54"		[5500]				
	"60"		5500				
	"66"		[6000[2]]				
	"85"		6000[2]				
	"Wide Body"		6000[2]				

ertification Standards

NMHC: 0.39
CO: 7.0
NOX: 0.7
VAP: 2.0

] Test at 5500lb. ETW per CFR 40.86-129-80.
] HP used to determine DPA is Frontal Area.

Revisions: 12-16-91