State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-23-159
Relating to Certification of New Motor Vehicles

HONDA MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Honda Motor Co., Ltd. exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: SHN1.5VJG2EA Displacement: 1.5 Liters (91 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Three Way Catalytic Converter
Heated Oxygen Sensor
Exhaust Gas Recirculation
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon Monoxide	Nitrogen Oxides	Formaldehyde
50,000	0.125	3.4	0.4	0.015
100,000	0.156	4.2	0.6	0.018

The TLEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon Monoxide	Nitrogen Oxides	Formaldehyde
50,000	0.076	0.3	0.2	0.002
100,000	0.086	0.3	0.2	0.002

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model-Year Passenger Cars, Light-duty Trucks, and Medium-Duty Vehicles with Three-Way Catalyst Systems and Feedback Control" (Title 13, California Code of Regulations, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models have been exempted from compliance with the "Malfunction and Diagnostic System Requirements-1994 and Subsequent Model-Year Passenger Cars, Light-duty Trucks, and Medium-Duty Vehicles and Engines" pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(2.0) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 18th day of July, 1994.

R. B. Summerfield
Assistant Division Chief
Mobile Source Division

E.O. # A-23-159

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer HONDA Exh Engine Family: SHN1.5VJG2EA

Evap Std: 50K X Useful Life with R/L___ Evap Engine Family: SHN1077BYM0C

Exh Std: Tier-0___ Tier-1___ TLEV X LEV___ ULEV___ ZEV___ ; EPA Tier-0___ Tier-1___

Veh Class(es): PC X LDT1___ LDT2___ MDV1___ MDV2___ MDV3___ MDV4___ MDV5___

Single Cert Std for Multi-Class Eng Fam: N/A

Exh Cert Fuel(s): Indo X Ph2___ Diesel: 13 CCR 2282___ or 40 CFR 86.113-90___ or -94___
M85___ CNG___ LPG___ Other___

Fuel Type(s): Dedicated X Flex-Fuel___ Dual-Fuel___ Gasoline X Diesel___ M85___
CNG___ LNG___ LPG___ Other___

Hybrid: Type A___ B___ C___, APU Cycle ___

Engine Configuration: L-4 Displacement: 1.5 Liters 91 Cubic Inches

Engine: Front X Mid ___ Rear ___ Drive: FWD X RWD ___ 4WD-FT ___ 4WD-PT ___

Exhaust ECS: TWC/HO2S/EGR/SFI

Engine Code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type A-automatic M-manual	ETW	DPA	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
SJL1 (CA)	Civic HB VX	M	2375	5.6 (DU)	EI Distributor: TD-42U ECM:37820-P07 -L02	EGR Valve: 11E	SA
SJL1/1 (CA)	Civic HB VX			6.2 (DU)			