State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-9-362
Relating to Certification of New Motor Vehicles

CHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That Chrysler Corporation 1997 model-year exhaust emission control systems are certified as described below for medium-duty vehicles:

Fuel Type: Gasoline

Engine Family: VCR360H8G1EL Displacement: 5.2 Liters (318 Cubic Inches)
5.9 Liters (360 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Three Way Catalytic Converter
Heated Oxygen Sensors (two)
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Test Weight (lbs.)	Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
3751-5750	50,000	0.32	4.4	0.7	12.5
	120,000	0.46	6.4	0.98	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Test Weight (lbs.)	Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
3751-5750	50,000	0.21	2.6	0.4	7.5
	120,000	0.23	3.2	0.53	n/a

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 2nd day of July 1996.

Raphael Susnowitz

for R. B. Summerfield
Assistant Division Chief
Mobile Source Division

E.O. # A-9-362
Page 1 of 2

1997 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Chrysler Corporation Exh Eng Fam: VCR360H8G1EL Evap Fam: VCR1073AYP0B / VCR1090AYP0B

All Eng Codes in Eng Fam: CA X 49S ____ 50S ____ AB965 ____
Exh Std: CA Tier-1 X TLEV ____ LEV ____ ULEV ____ ZEV ____; US EPA Tier-1 ____
Evap Std: 50K X Useful Life with R/L ____ In-Use Exh Std: Full In Use X Alt In Use ____
Veh Class(es): PC ____ LDT1 ____ LDT2 ____ MDV1 ____ MDV2 X MDV3 ____ MDV4 ____ MDV5 ____
Single Cert Std for Multi-Class Eng Fam: N/A (Specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated X Flex-Fuel ____ Dual-Fuel ____ Bi-Level ____ Gasoline X Diesel ____
CNG ____ LNG ____ LPG ____ M85 ____ Other (specify) ____
Emis Test Fuel(s): Indo ____ Ph2 X CNG ____ LPG ____ M85 ____ Other(specify) ____
Diesel: 13 CCR 2282 ____ or 40 CFR 86.113-90 ____ or 40 CFR 86.113-94 ____
Service Accum: Std AMA ____ Mod AMA X Mfr ADP ____ Other (Specify) ____
NMOG Test Procedure: N/A X Std ____ Equiv ____ R/L Test Proce: SHED ____ Pt Source ____
Hybrid: Type A ____ B ____ C ____, APU Cycle (e.g., Otto, Diesel, Turbine) ____
Engine Configuration: V-8 Displacement: 5.2 / 5.9 Liters 318 / 360 Cubic Inches
Valves per Cylinder: 2 Rated HP: 215 / 230 @ 4000/4000 RPM
Engine: Front X Mid ____ Rear ____ Drive: FWD ____ 4WD-FT ____ 4WD-PT X
Exhaust ECS (eg., EGR, MFI, TC, CAC): TWC, HO2S(2), OBD II, SFI
(use abbreviations per SAE J1930 SEP91)

Engine Code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type M5 A4	ETW or Test Wt.*	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalyst Converter Part No.
CA-100 (CA)	AB1L12 AB2L11	A3	5250	SEE ATTACHED	56040059D		52022022
	AB2L12 AB2L13		5500				
CA-200 (CA)	AB1L12 AB1L51 AB2L11	A4	5250		56040057D		
	AB2L12 AB2L13 AB2L52		5500				

* Test weights reflect ALVW.
Date Issued: 5/28/96

Revisions: 06/26/96

TH04-SDS/97

E.O. # A-9-362

1997 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS. LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES
(cont'd.)

Manufacturer: Chrysler Corporation Exh Eng Fam: VCR360H8G1EL Evap Fam: VCR1073AYP0B
VCR1090AYP0B

Engine Code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type M5 A4	ETW or Test Wt.*	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalyst Converter Part No.
CA-300 (CA)	AB2L12 AB2L52	A4	5500	SEE ATTACHMENT	56040073	None	52022022
CA-400 (CA)	BR1L31 BR1L32 BR1L61 BR1L62		5500		56040070D		52103198
CA-500 (CA)	BR6L61 BR6L62		5500				
CA-600 (CA)	BR1L31 BR1L32 BR1L61 BR1L62		5500		56040077		
CA-700 (CA)	BR6L61 BR6L62		5500				
CA-800 (CA)	AN1L61 AN1L62		5000		56040134A		52109300
CA-850 (CA)	AN1L61 AN1L62		5000				

* Test Weights reflect ALW.

Date Issued: 5/28/96

Revisions: 06/26/96

TH04-SDS/97

MODELS COVERED BY CERTIFICATE

Vehicle MFR: CHRYSLER

Engine Family: VCR360H8G1EL
Evaporative Fam: VCR1073AYPOB

Certificate #:

Model ID	Car Line	California Sales
BR1L31	Ram 1500 Pickup 2WD	YES
BR1L32	Ram 1500 Pickup 2WD	YES
BR1L61	Ram 1500 Pickup 2WD	YES
BR1L62	Ram 1500 Pickup 2WD	YES
BR6L61	Ram 1500 Pickup 4WD	YES
BR6L62	Ram 1500 Pickup 4WD	YES
AB1L12	Ram Van 1500 2WD	YES
AB2L12	Ram Van 2500 2WD	YES
AB2L13	Ram Van 2500 2WD	YES
AB2L11	Ram Van 2500 2WD	YES
AB1L51	Ram Wagon 1500 2WD	YES
AB2L52	Ram Wagon 2500 2WD	YES

Model Codes
BR 2 L 62

- 1st digit: 3=Club Cab, 6=Regular Cab
- 2nd digit: 1=119" or 139" wb; 2=135" or 155" wb; 3=139" wb Chassis Cab; 4=163" wb Chassis Cab
- Price Class: L=Covers all trim levels; C=Chassis Cab
- Model: 1=1500, 2=2500, 3=3500, 6=1500 4X4, 7=2500 4X4, 8=3500 4X4
- Body Code: Ram Pickup; Ram Club Cab; Ram Chassis Cab

Model Codes
AB 1 L 11

- 1st digit: 1=Van, 5=Wagon
- 2nd digit: 1=109.6" wb; 2=127.6" wb; 3=127.6" maxi wb
- Price Class
- Model: 1=B1500; 2=B2500; 3=B3500
- Body Code: Vans; Wagons

MODELS COVERED BY CERTIFICATE

Vehicle MFR: CHRYSLER

Engine Family: VCR360H8G1EL
Evaporative Fam: VCR1080AYP08

Certificate #:

Model ID	Car Line	California Sales
AN1L61	Dakota Pickup 2WD	YES
AN1L62	Dakota Pickup 2WD	YES

Model Codes

```
AN 1 L  31
|  |  |  |
|  |  |  --- 1st digit:      2nd digit:
|  |  |      3=Club Cab      1=119" or 130.9" wb
|  |  |      6=Regular Cab   2=123.9" wb
|  |  ------ Price Class
|  -------- Model:
|           1=2 wheel drive
|           5=4 wheel drive
------------ Body Code:
             Dakota Pickup
```

1997
VCR360H8G1EL

Chrysler Corporation
Family Tire Usage

MODEL	ENG	TRANS	A C	GVW	MKT TYPE	LVW	TIRE DESCRIPTION USE	YR	COD	MFG	OPT	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R	LOADED VEHICLE WEIGHT: TARGET A	B	C	SET A	B	C	(LINE 1 IS 20 DEG COEFFS, LINE 2 IS 50 DEG WHEN NEEDED)	ADJUSTED LOADED VEHICLE WGT: ALVW	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R
AB1L12	ELF	DGH	RW Y	6010	C	4500	STD	97	TSC	TZH		13.18	16.5	35	35								5250	15.22	15.5	35	35
							OPT	97	TSF	TZA		12.83	16.9	35	35									14.53	16.5	35	35
							OPT	97	TW9	TZA		12.46	15.3	35	35									13.78	14.1	35	35
AB1L12	ELF	DGT	RW Y	6010	C	4750	STD	97	TSC	TZH		13.87	16.6	35	35								5250	15.22	15.5	35	35
							OPT	97	TSF	TZA		13.50	17.0	35	35									14.53	16.5	35	35
							OPT	97	TW9	TZA		13.11	15.4	35	35									13.78	14.1	35	35
AB1L51	ELF	DGT	RW Y	6010	C	5000	STD	97	TSC	TZH		14.39	15.9	35	35								5250	15.22	15.5	35	35
							OPT	97	TSD	TZA		13.98	16.4	35	35									14.53	16.5	35	35
							OPT	97	TSD	TZH		14.39	15.9	35	35									15.22	15.5	35	35
							OPT	97	TSF	TZA		13.98	16.4	35	35									14.53	16.5	35	35
							OPT	97	TW9	TZA		13.58	14.2	35	35									13.78	14.1	35	35
AB2L11	ELF	DGH	RW Y	6400	C	4500	STD	97	TSC	TZH		13.18	16.5	35	35								5250	15.22	15.5	35	35
							OPT	97	TSD	TZA		12.83	16.9	35	35									14.53	16.5	35	35
							OPT	97	TSD	TZH		13.18	16.5	35	35									15.22	15.5	35	35
							OPT	97	TSF	TZA		12.83	16.9	35	35									14.53	16.5	35	35
							OPT	97	TW9	TZA		12.46	15.3	35	35									13.78	14.1	35	35
AB2L11	ELF	DGT	RW Y	6400	C	4750	STD	97	TSC	TZH		13.87	16.6	35	35								5250	15.22	15.5	35	35
							OPT	97	TSD	TZA		13.50	17.0	35	35									14.53	16.5	35	35
							OPT	97	TSD	TZH		13.87	16.6	35	35									15.22	15.5	35	35
							OPT	97	TSF	TZA		13.50	17.0	35	35									14.53	16.5	35	35
							OPT	97	TW9	TZA		13.11	15.4	35	35									13.78	14.1	35	35
AB2L12	ELF	DGH	RW Y	6400	C	4750	STD	97	TSC	TZH		13.87	16.6	35	35								5500	15.75	15.3	35	35
							OPT	97	TSD	TZA		13.50	17.0	35	35									15.01	16.3	35	35
							OPT	97	TSD	TZH		13.87	16.6	35	35									15.75	15.3	35	35
							OPT	97	TSF	TZA		13.50	17.0	35	35									15.01	16.3	35	35
							OPT	97	TW9	TZA		13.11	15.4	35	35									14.25	13.5	35	35
AB2L12	ELF	DGH	RW Y	6800	C	4750	STD	97	TSC	TZH		13.87	16.6	35	35								5500	15.75	15.3	35	35
							OPT	97	TSD	TZA		13.50	17.0	35	35									15.01	16.3	35	35
							OPT	97	TSD	TZH		13.87	16.6	35	35									15.75	15.3	35	35
							OPT	97	TSF	TZA		13.50	17.0	35	35									15.01	16.3	35	35
							OPT	97	TW9	TZA		13.11	15.4	35	35									14.25	13.5	35	35
AB2L12	ELF	DGT	RW Y	6400	C	4750	STD	97	TSC	TZH		13.87	16.6	35	35								5500	15.75	15.3	35	35
							OPT	97	TSD	TZA		13.50	17.0	35	35									15.01	16.3	35	35
							OPT	97	TSD	TZH		13.87	16.6	35	35									15.75	15.3	35	35
							OPT	97	TSF	TZA		13.50	17.0	35	35									15.01	16.3	35	35
							OPT	97	TW9	TZA		13.11	15.4	35	35									14.25	13.5	35	35
AB2L12	ELF	DGT	RW Y	6800	C	4750	STD	97	TSC	TZH		13.87	16.6	35	35								5500	15.75	15.3	35	35
							OPT	97	TSD	TZA		13.50	17.0	35	35									15.01	16.3	35	35
							OPT	97	TSD	TZH		13.87	16.6	35	35									15.75	15.3	35	35
							OPT	97	TSF	TZA		13.50	17.0	35	35									15.01	16.3	35	35
							OPT	97	TW9	TZA		13.11	15.4	35	35									14.25	13.5	35	35
AB2L12	EML	DGT	RW Y	6400	C	4750	STD	97	TSC	TZH		13.87	16.6	35	35								5500	15.75	15.3	35	35
							OPT	97	TSD	TZA		13.50	17.0	35	35									15.01	16.3	35	35

* - For DYNO HP = 0.00
Ref To FRONTAL AREA

/ 10. - TH04 - 400 /

Report Date: 06/05/96
Time: 10:15:52

1997
VCR360H8G1EL

Chrysler Corporation
Family Tire Usage

MODEL	ENG	TRANS	A C	GVW	MKT TYPE	LVW	TIRE DESCRIPTION USE	YR	COD	MFG	OPT	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R	LOADED VEHICLE WEIGHT: TARGET A (LINE 1 IS 20 DEG	B COEFFS,	C	COLD CO ELECTRIC DYNO COEFFICIENTS: SET A (LINE 2 IS 50 DEG	B WHEN	C NEEDED)	ALVW	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R
							OPT	97	TSD	TZH		13.87	16.6	35	35								15.75	15.3	35	35
							OPT	97	TSF	TZA		13.50	17.0	35	35								15.01	16.3	35	35
							OPT	97	TW9	TZA		13.11	15.4	35	35								14.25	13.5	35	35
AB2L12	EML	DGT	RW Y	6800	C	4750	STD	97	TSC	TZH		13.87	16.6	35	35							5500	15.75	15.3	35	35
							OPT	97	TSD	TZA		13.50	17.0	35	35								15.01	16.3	35	35
							OPT	97	TSD	TZH		13.87	16.6	35	35								15.75	15.3	35	35
							OPT	97	TSF	TZA		13.50	17.0	35	35								15.01	16.3	35	35
							OPT	97	TW9	TZA		13.11	15.4	35	35								14.25	13.5	35	35
AB2L13	ELF	DGH	RW Y	6400	C	4750	STD	97	TSC	TZH		13.87	16.6	35	35							5500	15.75	15.3	35	35
							OPT	97	TSD	TZA		13.50	17.0	35	35								15.01	16.3	35	35
							OPT	97	TSD	TZH		13.87	16.6	35	35								15.75	15.3	35	35
							OPT	97	TSF	TZA		13.50	17.0	35	35								15.01	16.3	35	35
							OPT	97	TW9	TZA		13.11	15.4	35	35								14.25	13.5	35	35
AB2L13	ELF	DGT	RW Y	6400	C	5000	STD	97	TSC	TZH		14.39	15.9	35	35							5500	15.75	15.3	35	35
							OPT	97	TSD	TZA		13.98	16.4	35	35								15.01	16.3	35	35
							OPT	97	TSD	TZH		14.39	15.9	35	35								15.75	15.3	35	35
							OPT	97	TSF	TZA		13.98	16.4	35	35								15.01	16.3	35	35
							OPT	97	TW9	TZA		13.58	14.2	35	35								14.25	13.5	35	35
AB2L52	ELF	DGT	RW Y	6400	C	5250	STD	97	TSC	TZH		14.87	16.0	35	35							5500	15.75	15.3	35	35
							OPT	97	TSD	TZA		14.41	16.5	35	35								15.01	16.3	35	35
							OPT	97	TSD	TZH		14.87	16.0	35	35								15.75	15.3	35	35
							OPT	97	TSF	TZA		14.41	16.5	35	35								15.01	16.3	35	35
							OPT	97	TW9	TZA		14.01	14.2	35	35								14.25	13.5	35	35
AB2L52	EML	DGT	RW Y	6400	C	5500	STD	97	TSC	TZH		15.41	16.2	35	35							5500	15.75	15.3	35	35
							OPT	97	TSD	TZA		14.92	16.7	35	35								15.01	16.3	35	35
							OPT	97	TSD	TZH		15.41	16.2	35	35								15.75	15.3	35	35
							OPT	97	TSF	TZA		14.92	16.7	35	35								15.01	16.3	35	35
							OPT	97	TW9	TZA		14.50	14.3	35	35								14.25	13.5	35	35
AN1L61	ELF	DGT	RW Y	6240	C	4000	STD	97	TS1	TZA		12.31	14.8	35	35							5000	14.61	12.9	35	35
AN1L61	ELF	DGW	RW Y	6240	C	4000	STD	97	TS1	TZA		12.50	14.7	35	35							5000	14.81	12.9	35	35
AN1L62	ELF	DGT	RW Y	6340	C	4000	STD	97	TS1	TZA		12.31	14.8	35	35							5000	14.61	12.9	35	35
AN1L62	ELF	DGW	RW Y	6340	C	4000	STD	97	TS1	TZA		12.50	14.7	35	35							5000	14.81	12.9	35	35
BR1L31	ELF	DGT	RW Y	6400	C	5000	STD	97	TRY	TZA		14.80	15.4	35	35							5500	15.98	15.0	35	35
							OPT	97	TYF	TZA		14.99	15.4	35	35								16.09	15.2	35	35
							OPT	97	TYG	TZA		14.67	15.7	35	35								15.73	15.7	35	35
							OPT	97	TYK	TZA		14.57	15.9	35	35								15.71	15.4	35	35
BR1L31	EML	DGT	RW Y	6400	C	5000	STD	97	TRY	TZA		14.80	15.4	35	35							5500	15.98	15.0	35	35
							OPT	97	TYF	TZA		14.99	15.4	35	35								16.09	15.2	35	35
							OPT	97	TYG	TZA		14.67	15.7	35	35								15.73	15.7	35	35
							OPT	97	TYK	TZA		14.57	15.9	35	35								15.71	15.4	35	35
BR1L32	ELF	DGT	RW Y	6400	C	5000	STD	97	TRY	TZA		14.80	15.4	35	35							5500	15.98	15.0	35	35
							OPT	97	TYF	TZA		14.99	15.4	35	35								16.09	15.2	35	35
							OPT	97	TYG	TZA		14.67	15.7	35	35								15.73	15.7	35	35

* - For DYNO HP = 0.00
Ref To FRONTAL AREA

Report Date: 06/05/96
Time: 10:15:52

1997
VCR360H8G1EL

Chrysler Corporation
Family Tire Usage

MODEL	ENG	TRANS	A C	GVW	MKT TYPE	LVW	TIRE DESCRIPTION USE	YR	COD	MFG	OPT	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R	LOADED VEHICLE WEIGHT: TARGET (LINE 1 IS 20 DEG COEFFS, LINE 2 IS 50 DEG WHEN NEEDED) A	B	C	SET A	B	C	ALVW	ADJUSTED LOADED VEHICLE WGT: COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R
							OPT	97	TYK	TZA		14.57	15.9	35	35								15.71	15.4	35	35
BR1L32	EML	DGT	RW Y	6400	C	5250	STD	97	TRY	TZA		15.41	15.4	35	35							5500	15.98	15.0	35	35
							OPT	97	TYF	TZA		15.84	15.4	35	35								16.09	15.2	35	35
							OPT	97	TYG	TZA		15.30	15.8	35	35								15.73	15.7	35	35
							OPT	97	TYK	TZA		15.20	16.0	35	35								15.71	15.4	35	35
BR1L61	ELF	DGT	RW Y	6400	C	4750	STD	97	TRY	TZA		14.37	15.2	35	35							5500	15.98	*15.0	35	35
							OPT	97	TYF	TZA		14.50	15.3	35	35								16.09	15.2	35	35
							OPT	97	TYG	TZA		14.20	15.7	35	35								15.73	15.7	35	35
							OPT	97	TYK	TZA		14.10	15.9	35	35								15.71	15.4	35	35
BR1L61	EML	DGT	RW Y	6400	C	4750	STD	97	TRY	TZA		14.37	15.2	35	35							5500	15.98	15.0	35	35
							OPT	97	TXP	TZA		12.79	15.1	35	35								14.17	14.5	35	35
							OPT	97	TYF	TZA		14.50	15.3	35	35								16.09	15.2	35	35
							OPT	97	TYG	TZA		14.20	15.7	35	35								15.73	15.7	35	35
							OPT	97	TYK	TZA		14.10	15.9	35	35								15.71	15.4	35	35
BR1L62	ELF	DGT	RW Y	6400	C	4750	STD	97	TRY	TZA		14.37	15.2	35	35							5500	15.98	15.0	35	35
							OPT	97	TYF	TZA		14.50	15.3	35	35								16.09	15.2	35	35
							OPT	97	TYG	TZA		14.20	15.7	35	35								15.73	15.7	35	35
							OPT	97	TYK	TZA		14.10	15.9	35	35								15.71	15.4	35	35
BR1L62	EML	DGT	RW Y	6400	C	4750	STD	97	TRY	TZA		14.37	15.2	35	35							5500	15.98	15.0	35	35
							OPT	97	TYF	TZA		14.50	15.3	35	35								16.09	15.2	35	35
							OPT	97	TYG	TZA		14.20	15.7	35	35								15.73	15.7	35	35
							OPT	97	TYK	TZA		14.10	15.9	35	35								15.71	15.4	35	35
BR6L61	ELF	DGT	4W Y	6400	C	5000	STD	97	TWA	TZH		12.61	15.6	40	35							5500	13.63	14.4	50	50
							OPT	97	TXE	TZA		12.04	15.9	35	35								12.61	15.7	40	40
							OPT	97	TXW	TZA		13.02	15.3	35	35								13.74	15.1	45	45
							OPT	97	TYK	TZA		12.69	16.7	35	35								13.85	15.5	50	50
							OPT	97	TYL	TZA		12.23	16.8	35	35								13.37	15.5	45	45
							OPT	97	TYM	TZA		12.23	16.8	35	35								13.37	15.5	45	45
							OPT	97	TYW	TZA		13.25	16.1	35	35								14.39	15.9	50	50
BR6L61	EML	DGT	4W Y	6400	C	5250	STD	97	TWA	TZH		13.17	15.7	40	35							5500	13.63	14.4	50	50
							OPT	97	TXE	TZA		12.58	15.9	35	35				67.34	-2.3500	0.0733		12.61	15.7	35	35
							OPT	97	TXW	TZA		13.60	15.4	35	35								13.74	15.1	35	35
							OPT	97	TYK	TZA		13.26	16.8	35	35								13.85	15.5	35	35
							OPT	97	TYL	TZA		12.78	16.9	35	35								13.37	15.5	35	35
							OPT	97	TYM	TZA		12.78	16.9	35	35								13.37	15.5	35	35
							OPT	97	TYW	TZA		13.85	16.2	35	35								14.39	15.9	35	35
BR6L62	ELF	DGT	4W Y	6400	C	5250	STD	97	TWA	TZH		13.17	15.7	40	35							5500	13.63	14.4	50	50
							OPT	97	TXE	TZA		12.58	15.9	35	35								12.61	15.7	40	40
							OPT	97	TXW	TZA		13.60	15.4	35	35								13.74	15.1	45	45
							OPT	97	TYK	TZA		13.26	16.8	35	35								13.85	15.5	45	45
							OPT	97	TYL	TZA		12.78	16.9	35	35								13.37	15.5	45	45
							OPT	97	TYM	TZA		12.78	16.9	35	35								13.37	15.5	45	45
							OPT	97	TYW	TZA		13.85	16.2	35	35								14.39	15.9	45	45

* - For DYNO HP = 0.00
Ref To FRONTAL AREA

/ 10. - TH04 - 402 /

Report Date: 06/05/96
Time: 10:15:52

1997
VCR360H8G1EL

Chrysler Corporation
Family Tire Usage

LOADED VEHICLE WEIGHT

ADJUSTED LOADED VEHICLE WGT

MODEL	ENG	TRANS	A C	GVW	MKT TYPE	LVW	TIRE DESCRIPTION USE	YR	COD	MFG	OPT	COAST DOWN TIME	*DYNO HP	TIRE PRES F	R	COLD CO ELECTRIC DYNO COEFFICIENTS TARGET A B C SET A B C (LINE 1 IS 20 DEG COEFFS,LINE 2 IS 50 DEG WHEN NEEDED)	ALVW	COAST DOWN TIME	*DYNO HP	TIRE PRES F	R
BR6L62	EML	DGT	4W Y	6400	C	5250	STD	97	TWA	TZH		13.17	15.7	40	35		5500	13.63	14.4	40	35
							OPT	97	TXE	TZA		12.58	15.9	35	35			12.61	15.7	35	35
							OPT	97	TXW	TZA		13.60	15.4	35	35			13.74	15.1	35	35
							OPT	97	TYK	TZA		13.26	16.8	35	35			13.85	15.5	35	35
							OPT	97	TYL	TZA		12.78	16.9	35	35			13.37	15.5	35	35
							OPT	97	TYM	TZA		12.78	16.9	35	35			13.37	15.5	35	35
							OPT	97	TYW	TZA		13.85	16.2	35	35			14.39	15.9	35	35

* - For DYNO HP = 0.00
Ref To FRONTAL AREA

/ 10. - TH04 - 403 /

Report Date: 06/05/96
Time: 10:15:52

1997
VCR36OH8G1EL

Chrysler Corporation
FAMILY TIRE DESCRIPTION

TIRE DESCRIPTION YR	COD	MFG	OPT	NAME	SIZE	RPM	CONSTRUCTION COD	TREAD MATERIAL	PLY	SW	SIDEWALL MATERIAL	PLY	OVERLAY MATERIAL	PLY	TREAD DEPTH (IN.) X 1/32
97	TRY	TZA		WRANGLER AP (A/S)	P225/75R16-XL	711	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	11
97	TS1	TZA		WRANGLER RTS (A/T)	P235/75R15	719	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	13
97	TSC	TZH		XW4 (A/S)	P235/75R15-XL	720	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	10
97	TSD	TZA		INVICTA-GL (A/S)	P235/75R15-XL	724	SBR	2-Steel/2-Polyester	4	WSW	Polyester	2	Nylon	1	10
97	TSD	TZH		XW4 (A/S)	P235/75R15-XL	720	SBR	2-Steel/2-Polyester	4	WSW	Polyester	2	None	0	10
97	TSF	TZA		INVICTA-GL (A/S)	P235/75R15-XL	724	SBR	2-Steel/2-Polyester	4	OWL	Polyester	2	None	0	10
97	TW9	TZA		WRANGLER AT (A/S)	LT235/75R15-D	716	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	13
97	TWA	TZH		LTX (A/S)	LT225/75R16-C	712	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	13
97	TXE	TZA		WRANGLER (A/T)	LT265/75R16-C	661	SBR	2-Steel/2-Polyester	4	OWL	Polyester	2	None	0	17
97	TXP	TZA		EAGLE GT II (A/SP)	P275/60R17	697	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	Nylon	2	11
97	TXW	TZA		WRANGLER RTS A/T	P265/75R16	660	SBR	2-Steel/2-Polyester	4	OWL	Polyester	2	None	0	11
97	TYF	TZA		WRANGLER AP (A/S)	P245/75R16	687	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	12
97	TYG	TZA		WRANGLER AP (A/S)	P245/75R16	687	SBR	2-Steel/2-Polyester	4	OWL	Polyester	2	None	0	12
97	TYK	TZA		WRANGLER RT/S(A/S)	LT245/75R16-C	683	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	14
97	TYL	TZA		WRANGLER RT/S(A/T)	LT245/75R16-C	679	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	16
97	TYM	TZA		WRANGLER AT (A/T)	LT245/75R16-C	679	SBR	2-Steel/2-POLYESTER	4	OWL	Polyester	2	None	0	16
97	TYW	TZA		WRANGLER RTS A/S	P245/75R16	687	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	11

Report Date: 06/05/96
Time: 10:15:52