State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-259-56
Relating to Certification of New Motor Vehicles

SUZUKI MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Suzuki Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VSK1.6VHGFEK Displacement: 1.6 Liters (97 Cubic inches)

Exhaust Emission Control Systems & Special Features:

Multiport Fuel Injection
Heated Oxygen Sensors (Two)
Warm Up Three Way Catalytic Converter
Three Way Catalytic Converter
Exhaust Gas Recirculation

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Mile	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Mile	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
50,000	0.11	0.6	0.1	2.4
100,000	0.12	0.7	0.1	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 16th day of July 1996.

R. B. Summerfield
Assistant Division Chief
Mobile Source Division

E.O.# A-259-56

1997 MODEL YEAR AIR RESOURCE BOARD **SUPPLEMENTAL DATA SHEET**
PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer: **SUZUKI MOTOR CORP** Exh Eng Fam: **VSK1.6VHGFEK** EVAP Fam: **VSK1030BYMA1**
All Engine Codes in Eng Fam: CA_X_49S_X_50S ____
Exh Std: Tier 0 ___ Tier 1_X_TLEV___ LEV ___ULEV____ZEV____; US EPA_____ Tier 1___X____
EVAP Std : 50K _X___ Useful Life with R/L_____ In Use Exh Std: FULL In Use_X_Alt In Use_____
Veh Class(es): PC_X_LDT1__LDT2___ MDV1__ MDV2____ MDV3____ MDV4 ____MDV5 ___
Single Cert Std for Multi-Class Eng Fam: ____ (specify: N/A, LDT1, LDT2,MDV1,MDV2,MDV3,MDV4,MDV5)
Fuel Type (s): Dedicated_____ Flex-Fuel _____ Dual-Fuel _____ Bi-Fuel ____ Gasoline _X_ Diesel _____
CNG_____ LNG _____ LPG _____ M85 ____ Other (specify) _____
Emiss Test Fuel (s): Indo ____ Ph2 _X_ CNG ____ LPG _____ M85_____ Other (specify)_____
Diesel: 13CCR 2282 _____ 40CFR 86.113-90 ____ 40CFR 86.113-94 _____
Service Accum: Std AMA _X___ Mod AMA _____ Mfr ADP _____ Other (specify)_____
NMOG Test Procedure : N/A _____ Std _____ Equiv _____ R/L Test Proc: SHED _____ Pt Source _____
Hybrid: Type A _____ B _____ C _____, APU Cycle (e.g. Otto, Diesel, Turbine) _____
Engine configuration: L4 (in line) Displacement: 1.6 Liters or 97 cubic inches
Valves per Cylinder: 4 Rated HP 98 @ 6,000 RPM
Engine: Front _X_ Mid___ Rear ____ Drive: FWD _X_ RWD ___ 4WD-FT ____ 4WD-PT _____.
Exhaust ECS (eg., EGR, MFI, TC, CAC): MFI / HO2S / WUTWC+TWC / EGR
(per SAE J1930 SEP91)

Engine Code (also list A/49ST/50ST)	Vehicle Models (re: p.21.00)	Trans type	ETW	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
CVCEM (CA,NY,MA)	ESTEEM	M5	2500	7.5	33920-61G4	18111-60G00	14240-60G00 (manifold) 14150-60G10 (under floor)
CVCEB (CA,NY,MA)		A4	2625	7.6	33920-61G5		
FVCEM (Federal)		M5	2500	7.5	33920-61G4		
FVCEB (Federal)		A4	2625	7.6	33920-61G5		

Date Issued: 31MAR96
Revised:

PV17EJ3.56