Fele



State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-6-1046
Relating to Certification of New Motor Vehicles

GENERAL MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below:

Model Year: 2002

Vehicle Type: 5751-8500 Pound Adjusted Loaded Vehicle Weight Medium-Duty Vehicle

Exhaust Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Test Group: 2GMXA04.8184

Engine Displacement: 4.8 Liters

Evaporative Family (Evap): 1: 2GMXE0111911
2: 2GMXE0133916

Special Features and Exhaust Emission Control Systems:

Sequential Multiport Fuel Injection
Dual Warm Up Three Way Catalytic Converters
Dual Three Way Catalytic Converters
Dual Heated Oxygen Sensors (two)

Models Covered:
Evap 1: Chevrolet C1500 Tahoe 2WD, K1500 Tahoe 4WD; GMC C1500 Yukon 2WD, K1500 Yukon 4WD
Evap 2: Chevrolet K1500 Silverado 4WD; GMC K1500 Sierra 4WD

The exhaust certification emission levels and standards, in grams per mile, of non-methane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) for the listed vehicle models are as follows. The NMOG exhaust certification emission levels include application of the reactivity adjustment factor (RAF) as specified.

The evaporative hydrocarbon (HC) certification emission levels and standards for three-day diurnal plus hot soak (3D) and two-day diurnal plus hot soak (2D) in grams per test, running loss (RL) in grams per mile, and onboard refueling vapor recovery (ORVR) in grams per gallon of fuel dispensed, for the listed vehicle models are as follows.

| Type of Emissions | Miles | Certification Level | Certification Standards |
|---|---|---|---|
| EXHAUST @ NMOG RAF = 0.94 | | | |
| NMOG | 50,000 | 0.088 | 0.195 |
| NMOG | 120,000 | 0.088 | 0.280 |
| CO | 50,000 | 2.1 | 5.0 |
| CO | 120,000 | 2.1 | 7.3 |
| NOx | 50,000 | 0.2 | 0.6 |
| NOx | 120,000 | 0.2 | 0.9 |
| NOx (highway) | 50,000 | 0.2 | 1.2 |
| NOx (highway) | 120,000 | 0.2 | 1.8 |
| HCHO | 50,000 | 0.0005 | 0.022 |
| ..... HCHO | 120,000 | 0.0005 | 0.032 |
| ..... CO (20$^0$F) | 50,000 | 5.4 | 12.5 |
| NMOG (50$^0$F) | 4,000 | 0.160 | 0.390 |
| CO (50$^0$F) | 4,000 | 3.6 | 5.0 |
| NOx (50$^0$F) | 4,000 | 0.05 | 0.6 |
| HCHO (50$^0$F) | 4,000 | 0.001 | 0.044 |

| EVAPORATIVE | | Evap 1 | Evap 2 | Evap 1 | Evap 2 |
|---|---|---|---|---|---|
| HC-2D | 120,000 | 1.4 | 1.4 | 2.5 | 3.0 |
| HC-3D | 120,000 | 1.3 | 1.0 | 2.0 | 2.5 |
| HC-RL | 120,000 | 0.00 | 0.00 | 0.05 | 0.05 |
| HC-ORVR | 120,000 | n/a | n/a | n/a | n/a |

BE IT FURTHER RESOLVED: That any "Vehicle Equivalent Debit" in the manufacturer's medium-duty vehicle phase-in compliance plan shall be equalized as required by the "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1).

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with the following California emission regulations and requirements. Vehicles certified under this Executive Order shall conform to all applicable California emission regulations and requirements.

- Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks (Title 13, California Code of Regulations, Section 2235)

- Motor Vehicle Emission Control and Smog Index Label Specifications (Title 13, California Code of Regulations, Section 1965)

- Emission Control System Warranty (Title 13, California Code of Regulations, Sections 2035 et seq.)

- High-Altitude Requirements and California Inspection and Maintenance Emission Standards (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles)

The Bureau of Automotive Repair will be notified by copy of this order.

Executed at El Monte, California this 22nd day of February 2001.

FOR

R. B. Summerfield, Chief
Mobile Source Operations Division