

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED. The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GROUP	INFOR	MATION		n n shek ya ha shekara		
MODE		EST GROUP		VEHICLE CLASS(ES)			FUEL C	ATEGORY	FUEL TYPE		
2018	18 JFMKD06.761B			MDV4				SINGLE FUEL HICLE	DIESEL		
USEFUL LIFE (miles)				VEHICLE EMISSION CATEGOR			GORY	INTERIM / INT	RMEDIATE IN-USE STD		
EXH/ORVR EVAP				FTP		SF	TP	FTP	SFTP		
120000 *				LEV	72 ULEV *		*	*	. *		
SPE	CIAL FE	ATURES & EX			ON CONTROL	-	OBD S	TATUS	ENGINE DISPLACEMENT		
1	TC, DFI, CAC, EGR, EGRC, OC, DPF, SCRC, NOXS (2) RDQS						FULL	*			
*	*						PARTIAL *		6.7		
*			,	*		PARTIAL WITH FINES		ALL MODELS			
		E	VAP	ORATIVE &	REFUELING (EV	AP/OR	VR) FAMILY	INFORMATION	1		
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGO					STD CATEGOR	Y	EVAP EMISSION STD VEHICLE CLASS		SPECIAL FEATURES		
*				*				*	*		
				E	MISSION CRED	IT INFO	ORMATION				
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY				NMOG CREDIT FOR NON-PZEV ZERO-EVAP			NMOG CI	REDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS		
*					N			N	N		
				NMOG	AND FLEET AV	ERAG	E INFORMA	TION			
	CH4 FTP NMOG/NMHC RAF RATIO		CHO/NMHC RATIO NMOG+NOX FLEE LDT (3751 LVW-850 + MDPV (g/m		8500 G	00 GVW) MDV (8501-10000 GVW		NMOG+NOX FLEET ST( MDV (10,001-14,000 GVWR) (g/mi)			
*	*	*		*	*			*	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

## BE IT FURTHER RESOLVED:

The vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models has been determined to have four deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of one hundred dollars (\$100) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2018 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 10 ° day of November 2017.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

Executive Order: A-010-2102 New Passenger Cars, Light-Duty Trucks and FORD MOTOR CALIFORNIA Medium-Duty Vehicles COMPANY AIR RESOURCES BOARD Page 3 of 4 ATTACHMENT EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles: F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP FUEL TYPE NMHC CO NOx HCHO PM (g/mi) (g/mi) (g/mi) (mg/mi) (g/mi) CERT STD CERT STD CERT STD CERT STD CERT STD \* \* \* \* + \* -+ + FTP@50K • + FTP@UL 0.043 0.143 0.2 6.4 0.2 0.2 6.0 16 DIESEL-EPA 0.01 0.06 50°F @4K \* \* \* NOx (q/mi) CO (g/mi) FUEL TYPE CERT CERT STD STD \* \* \* HWFET @ 50K 0.1 0.4 HWFET @ UL DIESEL-EPA 20°F @ 50K \* \* SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS **US06** SC03 COMPOSITE FUEL TYPE NMHC+NOx co PM NMHC+NOx NMHC+NOx CO CO PM (g/mi) (g/mi) (mg/mi) (g/mi) (g/mi) (g/mi) (g/mi) (ma/mi) \* CERT \* \* \* 18 % @ 4K STD \* \* \* \* CERT \* 1 + \* \* \* + + \* STD + + + \* \* @ UL \* BIN . \* WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS WHOLE VEHICLE EVAPORATIVE TESTING EVAPORATIVE RL (g/mi) @ UL FUEL TYPE 3DHS (g/test) @ UL 2DHS (g/test) @ UL FAMILY CERT STD CERT STD FEL FEL CERT STD \* \* \* \* \* \* \* \* \* \* ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS FUEL ONLY EVAP & CANISTER BLEED ORVR (g/gallon) @ UL **EVAPORATIVE 3DHS RIG TEST** 2DHS RIG TEST **BLEED CANISTER** FAMILY (g/test) @ UL (g/test) @ UL TEST (g/test) @ 4K FUEL TYPE FUEL TYPE | CERT STD CERT CERT STD STD CERT STD

- +

\* EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES) EVAPORATIVE FAMILY LEAK FAMILY CERT STD \* \* \* \*

CALIFORNIA AIR RESOURCES BOARD

FORD MOTOR COMPANY Executive Order: A-010-2102 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

\* =not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; LDT1=LDT<6000#GVWR,0-3750#LVW; LDT2=LDT<6000#GVWR,3751-5750#LVW; LDT3=LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4=LDT 6001-8500#GVWR,5751 -8500#ALVW; MDV=medium-duty vehicle; MDV4=MDV 8501-10000#GVWR; MDV5=MDV 10001-14000#GVWR; MDPV=mediumduty passenger vehicle; ECS= emission control system; CERT= certification; STD= standard; FEL= family emission limit; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; PZEV=partial allowance zero-emission vehicle; AT PZEV=advanced technology PZEV; TZEV=transitional zero-emission vehicle; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3= selective catalytic reduction-urea/ammonia; NH3OC=ammonia oxidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DPF=diesel particulate filter (active); HO2S/O2S=heated/oxygen sensor; WR-HO2S or AFS=wide rage/linear/heated air-fuel ratio sensor; NOXS= NOx sensor; RDQS=reductant quality sensor; NH3S = ammonia sensor; EGR=exhaust gas recirculation; EGRC=EGR cooler; AIR/AIRE=secondary air injection (belt driven)/(electric driven); PAIR=pulsed AIR; SFI/MFI= sequential/ multiport fuel injection; DFI=direct fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD(F)/(P)(B)=full/partial/both on-board diagnostic; DOR=direct ozone reducing; HCT=hydrocarbon trap; BCAN=bleed carbon canister; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" ethanol ("15%"gasoline) fuel; E10="10%" ethanol ("90%"gasoline) fuel

## 2018 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	F250 2WD BED DELETE DIESEL	MDV4	6.7	SA6	*	1	\$
FORD	F250 4WD BED DELETE DIESEL	MDV4	6.7	SA6	*	1	\$
FORD	F250 PICKUP 2WD DIESEL	MDV4	6.7	SA6	*	1	\$
FORD	F250 PICKUP 4WD DIESEL	MDV4	6.7	SA6	*	1	\$
FORD	F350 2WD BED DELETE DIESEL	MDV4	6.7	SA6	*	1	\$
FORD	F350 2WD DIESEL	MDV4	6.7	SA6	*	1	\$
FORD	F350 4WD BED DELETE DIESEL	MDV4	6.7	SA6	*	1	\$
FORD	F350 4WD DIESEL	MDV4	6.7	SA6	*	1	\$